Test report

Light measurement results

Print date 17-11-2026

Laboratory and Equipment

Test lab	Viso LabSpion - serial: 3331725735 sensor serial: 3532797498 - T
Spectrometer Manufacturer and Model	LabSpion – Type C, horizontal
Measurement date	11/11/2026

Measurement Conditions

Tested c-planes	72 planes – 5,00°
Tested gamma resolution	1,00°
Input Power	12,18 W

Tested Light Source


Luminaire	GAMMA 10 SURFACE 3000K 24D WHITE
Basic Luminous Shape	SPOT
Item No.	04064900302403
Manufacturer	ELECTRUM
Description	300mA\line LED BRIDGELUX
Dimensions, luminous surface	H/D = -1,5, W = 0, L = 3,8, Shape = SPOT
Dimensions, light source housing	H/D = 7,1, W = 0, L = 5,3

Main Light Measurement Results

Output – Total Lumen (Up% / Down%)	1809 lm – 1,707% / 98,29%
Efficiency	148,5 lm/W
Peak Intensity	9180 cd
Correlated Color Temperature, CCT	3000 K
Color Rendering Index	CRI 94,6 TM30Rf 90,9 TM30 Rg 102,2

Polar light distribution diagram


Unit: 0-100% of peak intensity



Product photo



Spectral power distribution




Test report

Light measurement results

Print date 17-11-2026

Luminous Intensity diagram

Unit: 0-100% of peak intensity



Main Values

Output (total Lumen)	1809 lm
Lumen Up% / Down%	1,707% / 98,29%
Peak Intensity	9180 cd
Beam Angle (50%-FWHM)	22,4°

EU Ecodesign parameters


Directionality (DLS or NDLS)	DLS
Ecodesign Useful Luminous Flux	1694 lm
Ecodesign Energy Class	C

Intensity Ratio

In 120° cone	96,33%
In 90° cone	93,64%

Linear distribution diagram

Intensity [cd]




Test report

Light measurement results

Print date 17-11-2026


Iso-intensity Diagram (Iso-candela)



90 %	8204,0 cd
80 %	7292,5 cd
70 %	6380,9 cd
60 %	5469,4 cd
50 %	4557,8 cd
40 %	3646,2 cd
30 %	2734,7 cd
20 %	1823,1 cd
10 %	911,6 cd

Peak intensity: 9115,6 cd
Number of c-planes: 72

Iso-illuminance Diagram (Iso-lux)



50,0 %	506 lx
30,0 %	304 lx
10,0 %	101 lx
5,0 %	50,6 lx
3,0 %	30,4 lx

Peak illuminance: 1012 lx
Mounting height: 3 m
Number of c-planes: 72

Test report


Light measurement results

Print date 17-11-2026


Color details

Correlated Color Temperature, Target	CCT = 3000 K	MacAdam Steps	SDCM = 6,1
Correlated Color Temperature, Measured	CCT = 3064 K	Color deviation from BBL	Duv = -0,0054
Color Rendering Index	CRI 94,6	Color coordinates CIE 1931	(x;y) = (0,4372;0,4042)
Color Rendering Index, R9 (red)	R9 = 69,2	Color coordinate CIEs 1960	(u;v) = (0,2507;0,3476)
Color Rendering TM30-18	Rf 90,9	Color coordinate CIEs 1976	(u';v') = (0,2507;0,5215)
	Rg 102,2	Color Quality Scale	CQS = 90,4


CIE 1931 Chromaticity diagram




Spectral power distribution



CIE 1931 Chromaticity - zoomed




Color Rendering Index per reference color (CIE 1995)




CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
97,0	98,2	97,6	94,9	97,0	94,8	91,1	85,9	69,2	95,1	95,4	86,6	97,3	97,9	94,7

CIE 1931 Chromaticity - SDCM



TM30-18 Rf-values per hue bin




TM30-18 Rf-values per hue bin

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
91,6	92,7	87,2	92,9	92,6	91,6	93,6	96,1	95,8	92,0	89,3	86,6	86,6	85,5	88,7	84,9

Color details - ANSI/IES TM-30-18 Color Rendition Report


Color Vector Graphic




Color Distortion Graphic



Gamut Index vs. Fidelity Index




Color Rendition by Color Evaluation Sample (CES)




Color evaluation sample CES01 through CES99

Local Color Fidelity (per hue bin)



Local Chroma Shift (per hue bin)



CIE x	0,4372
CIE y	0,4372
CIE u'	0,2507
CIE v'	0,5215


CIE	13.3-1995
Ra	94,6
R9	69,2

Test report

Light measurement results


Print date 17-11-2026

Beam details



Luminaire budgetary diagram

LAMPS (number of lamps)



Intensity details

Beam intensities from 1 – 20 m

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	m
3,3	6,6	9,8	13,1	16,4	19,7	23	26,2	29,5	32,8	36,1	39,4	42,7	45,9	49,2	52,5	55,8	59,1	62,3	65,6	ft
9001	2250	1000	563	360	250	184	141	111	90	74	63	53	46	40	35	31	28	25	23	lux
836,2	209,1	92,9	52,3	33,4	23,2	17,1	13,1	10,3	8,4	6,9	5,8	4,9	4,3	3,7	3,3	2,9	2,6	2,3	2,1	fc

Intensities in 0° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
9001	8821	8148	7253	6276	5213	4091	3051	2175	1513	1041	735	530	390	290	221	170	135	109	89	cd
100%	98%	91%	81%	70%	58%	45%	34%	24%	17%	12%	8%	6%	4%	3%	2%	2%	2%	1%	1%	of 0°val

Intensities in 90° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
9001	8149	7560	6828	6051	5215	4263	3287	2386	1667	1131	775	549	404	303	231	179	142	114	94	cd
100%	91%	84%	76%	67%	58%	47%	37%	27%	19%	13%	9%	6%	4%	3%	3%	2%	2%	1%	1%	of 0°val

Intensities in 180° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
9001	8821	8148	7253	6276	5213	4091	3051	2175	1513	1041	735	530	390	290	221	170	135	109	89	cd
100%	98%	91%	81%	70%	58%	45%	34%	24%	17%	12%	8%	6%	4%	3%	2%	2%	2%	1%	1%	of 0°val

Intensities in 270° c-plane

0°	2°	4°	6°	8°	10°	12°	14°	16°	18°	20°	22°	24°	26°	28°	30°	32°	34°	36°	38°	γ
9001	8149	7560	6828	6051	5215	4263	3287	2386	1667	1131	775	549	404	303	231	179	142	114	94	cd
100%	91%	84%	76%	67%	58%	47%	37%	27%	19%	13%	9%	6%	4%	3%	3%	2%	2%	1%	1%	of 0°val

UGR Table

Corrected, comprehensive UGR table according to 117-1995, S/H ratio=0.25

Reflectances											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room size		**Viewed Crosswise**					**Viewed Endwise**				
H = mouting height above eye level		(Viewing direction orthogonal to lamp length axis)					(Viewing direction parallel to lamp length axis)				
X	**Y**										
2H	2H	19,2	19,6	19,3	19,8	20,1	19,2	19,6	19,3	19,8	20,0
	3H	19,8	20,4	20,2	20,6	20,8	19,7	20,3	20,1	20,6	20,8
	4H	20,1	20,7	20,6	21,0	21,2	20,1	20,7	20,5	21,0	21,2
	6H	20,6	21,1	20,9	21,4	21,8	20,6	21,1	20,9	21,4	21,8
	8H	20,8	21,3	21,2	21,7	22,1	20,9	21,3	21,2	21,7	22,1
	12H	21,1	21,6	21,5	21,9	22,4	21,2	21,6	21,5	22,0	22,4
4H	2H	19,3	19,9	19,7	20,1	20,4	19,3	19,9	19,7	20,1	20,4
	3H	20,3	20,8	20,7	21,1	21,6	20,3	20,7	20,7	21,1	21,6
	4H	20,8	21,2	21,2	21,6	22,2	20,7	21,2	21,2	21,6	22,1
	6H	21,3	21,8	21,9	22,2	22,5	21,3	21,8	21,8	22,1	22,5
	8H	21,6	22,1	22,2	22,4	22,8	21,6	22,1	22,2	22,4	22,8
	12H	22,0	22,4	22,6	22,8	23,3	22,1	22,4	22,6	22,8	23,3
8H	4H	20,9	21,4	21,5	21,7	22,1	20,9	21,4	21,5	21,7	22,1
	6H	21,7	22,0	22,2	22,5	23,0	21,7	22,0	22,2	22,5	23,0
	8H	22,2	22,4	22,8	23,0	23,6	22,2	22,4	22,8	23,0	23,6
	12H	22,8	23,0	23,4	23,5	24,2	22,8	23,0	23,5	23,6	24,2
12H	4H	20,9	21,3	21,5	21,7	22,2	20,9	21,3	21,4	21,7	22,2
	6H	21,9	22,1	22,4	22,6	23,3	21,8	22,1	22,4	22,6	23,2
	8H	22,4	22,5	23,0	23,1	23,7	22,4	22,6	23,0	23,1	23,7
Variations with the observer position for the luminaire spacings, S:											
S = 1.0H		0,6 / -0,3					0,6 / -0,3				
S = 1.5H		1,3 / -0,5					1,4 / -0,5				
S = 2.0H		2,2 / -0,8					2,2 / -0,8				

Coefficients of utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20
RCR	(Room Cavity Ratio)				Room values are expressed as percentage of Lumen delivered to the task surface													
0	118,6	118,6	118,6	118,6	115,7	115,7	115,7	115,7	110,2	110,2	110,2	105,1	105,1	105,1	100,5	100,5	100,5	98,3
1	114,1	111,7	109,6	107,7	111,5	109,4	107,6	105,9	105,1	103,7	102,3	101,2	100,0	99,0	97,5	96,6	95,9	94,0
2	109,9	105,9	102,6	99,8	107,6	104,1	101,1	98,6	100,7	98,3	96,2	97,5	95,6	93,9	94,6	93,1	91,8	90,2
3	106,0	100,9	97,0	93,8	104,0	99,4	95,9	93,0	96,7	93,7	91,3	94,2	91,7	89,7	91,8	89,8	88,2	86,7
4	102,4	96,6	92,3	89,0	100,7	95,4	91,5	88,4	93,2	89,9	87,2	91,1	88,3	86,1	89,2	86,9	85,0	83,6
5	99,1	92,8	88,3	85,1	97,6	91,8	87,7	84,6	90,0	86,5	83,8	88,3	85,3	82,9	86,7	84,1	82,1	80,8
6	96,1	89,4	84,9	81,7	94,7	88,6	84,4	81,4	87,1	83,4	80,7	85,7	82,5	80,1	84,3	81,6	79,5	78,3
7	93,2	86,4	81,9	78,8	92,0	85,7	81,5	78,5	84,4	80,7	78,1	83,2	80,0	77,6	82,1	79,3	77,1	76,0
8	90,6	83,6	79,2	76,2	89,5	83,1	78,9	76,0	82,0	78,3	75,6	81,0	77,7	75,3	80,0	77,1	74,9	73,8
9	88,1	81,1	76,8	73,9	87,2	80,6	76,6	73,8	79,7	76,0	73,5	78,8	75,5	73,2	78,0	75,0	72,9	71,9
10	85,9	78,8	74,6	71,8	85,0	78,4	74,4	71,7	77,6	74,0	71,5	76,9	73,6	71,2	76,1	73,2	71,0	70,0

Test report


Light measurement results

Print date 17-11-2026

Power details

Input power	
Frequency of input power	50,0 Hz
Power feed to light source	12,18 W
RMS Input voltage feed V,RMS	225,2 V
RMS Input current feed I,RMS	0,08 A
Volt-Amp or apparent power = V,RMS*I,RMS	18,8 VA
Displacement factor of AC power feed	0,85
Power factor of AC current feed	0,65
Total harmonic distortion of the current	77,81%
Total harmonic distortion of the voltage	5,333%

Input power curve




Efficiency

Radiated power efficiency	44,6
Lumen efficiency	148,5 lm/W

Stabilization details

Warmup Conditions		Color Temperature Change	
Stable period	15 min	CCT start	3062 K
Stable change max	2%	CCT shift	-62 K
Minimum time	15 min	CCT end	3000 K
Warmup Result		**Output Change**	
Total warmup time	Lamp stabilized in	Output start	1862 lm
Warmup variation	-2,8979%	Output change	-52,888 lm
		Output end	1809 lm

Stabilization Curve



Flicker TLA details

Flicker Meter Type	Viso Systems LabFlicker
Frequency of input power	50,0 Hz
Flicker/TLA sample rate	20,0 samples/s

Measurement time

PstLM	180 sec.
All other indices	1,5 sec,

Flicker indices according to Illuminating Engineering Society (IES)

Flicker frequency	99,5 Hz
Percent Flicker	0,4216 %
Flicker index	0,0

TLA indices (re IEC TR 61547-1, IEC 61000-3-3 and IEC 61000-4-15)

PstLM value (F < 80 Hz)	0,02
SVM value (80 < F < 2000 Hz)	0,01


Flicker indices according to California Energy Commission (CEC) 2016b

JA8/10 40 Hz	0,0599 %
JA8/10 90 Hz	0,0606 %
JA8/10 200 Hz	0,3962 %
JA8/10 400 Hz	0,4103 %
JA8/10 1000 Hz	0,4157 %


Flicker indices according to Lighting Research Center (2015)

Perception metric, Assist Mp	0,01

Flicker frame (frame of one flicker period in time domain)



Flicker FFT (flicker curve in frequency domain)



IEEE 1789 Frequency/modulation plot

